

SL15

Strip Light: 15W/m 24Vdc

Strip light with best SMDs for great lighting outcome, closely placed diodes for non-dotting effect with profiles & well performing circuit board for thermal management.


Light Emitting Diode

- **SAMSUNG 2835**
- CRI 90+ (R9:62+, R13:95+)
- 3 Step MacAdam
- Luminous Efficacy (lm/W)
128 at 3K-IP20
138 at 4K-IP20
- Life expectancy at 10,000hrs 54°C 75mA
Reported TM-21 L70: >60,000hrs
- Selection options:



Circuit Board

- White, Double layer, Cu (3oz)
- 3M Adhesive backing
- Cutting Unit: 33.33mm
- Reel Dimensions:
5000mmL*10mmW*2mmH
(4mmH for IP67 strip)




Electrical

- 15W/m (Max.) 24Vdc
- 240LEDs/m, 8LEDs/Circuit section
- 150mm 2C*18AWG feed cable
- Control (**Meanwell HLG & ELG**)
 - Non-Dim
 - 1-10V
 - DALI

Luminous Flux & Distribution

- 1951lm/m at 15W/m-3K-IP20
- 2092lm/m at 15W/m-4K-IP20



Responsibly Sourced Product

- High lm/w for great lighting & compliance with Std & BCA J-6.
- Paper Reel & Bag
- Lead-free soldering

Note: For desired life expectancy, it is recommended to install strip light in Al profile.
Ambient Operating Temp (Ta) -25°C to +50°C.

Order Code: SL15-3-20: 15W/m-3K-IP20
SL15-4-20: 15W/m-4K-IP20

SL15-3-67: 15W/m-3K-IP67
SL15-4-67: 15W/m-4K-IP67

(Information above is best known at publication & subject to change with improvements)

(+61) 451 916 586 | info@mydlight.com.au | www.mydlight.com.au