

## TL9040CT

### Track Light: 15W/25W 38°/60° CRI90 4-wire Connector Type

For superior color rendering, high illumination, deep recessed COB for glare control. Slim, cylindrical, adjustable. Double Earthing. Separate compartment for control gear.

#### Light Source

- **CREE-CXA/OSRAM** COB
- CRI 90 [R9-67, R13-93]
- 3 Step MacAdam
- Life expectancy @10,050hrs 55°C 577mA  
Reported TM-21 L70: >60,500hrs

#### LED Driver

- Tridonic Constant Current
- THD<15% PF 0.95 Eff. 90% at Full Load
- O/L, S/C, O/V, O/T Protection
- Life expectancy: up to 50,000hrs

#### Body

- Die-cast Aluminium
- Best designed heat sink
- Powder coated: Matt White/Black

#### Reflector & Diffuser Cover

- PC Reflector with Al Plating
- Clear PMMA diffuser
- 90% Efficiency at 38°/60°



#### Luminaire Details

- System Power **15W & 25W**
- Beam Angles : 38° & 60°
- IP20
- Dimming Controls:
 

Non Dim	DALI
1-10V Dim	CASAMBI

#### Luminaire Luminous Flux

1955lm at 25W-4K-38° [80lm/W]

3926.3	1m	4722.168	0.720
981.59	2m	1180.542	1.440
436.26	3m	524.685	2.160
245.40	4m	295.136	2.879
157.06	5m	188.887	3.599
Con E(lx)		Avg E(lx)	Dia (m)

Beam Angle: 39.6

#### Responsibly Sourced Product

- High lm/W for great lighting outcome & compliance with Standards & BCA J-6
- Easy & quick installation

#### Note:

Ambient Operating Temp (Ta) -20°C to +45°C.  
Suitable for 4-wire tracks (TR164ST) only.

**Order code:** TL9040CT-W[15/25]-CT[3K/4K]-Beam[38°/60°]-Color Finish[Black/White]-  
Control[Non Dim/Phase/1-10V/DALI]  
**For example:** [TL9040CT-15W-3K-60°-Black-Ph]